

Howotruck (Phils) Corporation

lain Office:

irgy. Bogtong, Diversion Road, Legazpi City

Manila Office:

28-D Himlayan Rd. Brgy Pasong Tamo, Tandang Sora, Quezon City Contact No. (02) 7344-6627 / 09177105690 Email: howophil@qmail.com

HOWO CARGO TRUCK 4x2, 180HP (20FT) EURO IV

Model:
Series:
Engine Power, HP
Wheel Traction/Drive Style:
Full Load Mass Weight:
Curb Mass/Self Weight:
Steering Wheel Position:

ZZ1167G471CD1
HOWO
180HP EURO IV
17,700 kg
17,700 kg
5,700 kg
LHD
(Left HandDrive)

Engine

Model: **SINOTRUK MAN ENGINE MC05.18-40**Displacement: 4.58L
Type: In-line, Four-cylinder, Turbocharged intercooler, high pressure common rail

Bore/Stroke: 108x125mm Net Power: 132kW/2400rpm Torque (Nm/rpm): 700N.m/1300 \sim 1700rpm

Axle & Suspension & Brake System

Front Axle:

Rear Axle:

Ratio of Rear Axle:

Suspension Type
(Front):

(Rear):

Brake (Service brake):

3.6T

8T

4.875

9pcs leaf spring
12+9pcs leaf spring
Air brake,drum brake

Wheels & Tires

All-cut off brake

Wheel Type: stud piloted 10 hole steel disc Number of Tires: 6+1 (spare tire) Tire Type/Size: 9.00R20 Track Front/Rear: 1801mm/1796mm

General Performance Parameters

Max Driving Speed: 95km/h
Average Fuel Consumption: ≤199g/kW.h
Max Gradeability: ≈30°
Cargo Tilt Box Angle: Loading Capacity: 12,000kg

Chassis & Dimensions

Overall Dimension 8500x2500x2850mm

(lengthxwidthxheight):

Wheel Base(mm): 4700mm

Vehicle Overhang: Front: 1240/Rear: 2505

Front Approach Angle: 17%

Rear Departure Angle: 20%

Gear Box Systems

Gear box: HW90510C, Manual Gearbox

(with high & low)

Gear speed/lever: 10forward/ 2 reverse Gear Ratio: 9.06,6.78,5.1,3.91,3.05,2.32,1.7 3,1.3,1,0.78,7.55(R1),3.91(R2)

Cargo Box SIZE (internal dimension)

LxWxH: 6100*2300*800mm
Floor Thickness: 3mm steel plate
Side Thickness: 1.5mm steel plate

Cabin

Cab: (2080 single and half row)

All-steel frame with 4-point support fully floating suspension and shock absorbers, Adjustable steering wheel, Heating and ventilating system, Exterior sun visor, Adjustable roof flap and Air horn

Electrical System

Battery: 135ah, 2 Quantity Alternator: 24V Operating Voltage: 24V

Fuel Tank

Capacity: 300L Shape/Structure: Rectangular/Aluminum

PHOTO FOR REFERENCE ONLY

Brake (Parking brake):



