



Howotruck (Phils) Corporation

Main Office:
Brgy. Bogtong, Diversion Road, Legazpi City

Manila Office:
28-D Himlayan Rd. Brgy Pasong Tamo, Quezon City
Contact No. 09177105690 / (02) 7344-6627
Email: howophil@gmail.com

HOWO 4x2 FUEL TRUCK 180HP EURO IV 6m³ (LIGHT TRUCK)

Chassis Model.....**ZZ1107G381CD1**
Series.....HOWO
Wheel Traction/Drive Style.....**4x2**
Rated Horse Power / Engine.....**180HP / EURO IV**
Total Mass.....16,500kg
Curb Mass/Self Weight.....6,500kg
Steering Wheel Position.....**LHD (Left Hand Drive)**

Engine

Model.....**SINOTRUK MAN ENGINE MC05.18-40**
Displacement.....4.58L
Type: In-line, Four-cylinder, Turbocharged intercooler, high pressure common rail
Bore/Stroke.....108x125mm
Net Power.....132kW/2400rpm
Torque.....700N.m/1300~1700rpm

Gear Box Systems

Gear Box.....HW90510C+PTO,**Manual Gearbox**
Gear Speed/Lever.....10forward/ 2 reverse
Gear
Ratio.....9.06,6.78,5.1,3.91,3.05,2.32,1.73,1.3,1, 0.78,7.55(R1),3.91(R2)

Axles & Suspension & Brake System

Front Axle.....3.2T
Rear Axle.....8T
Ratio of Rear Axle.....4.33
Suspension Type.....**Front:** 9pcs leaf spring
Rear: 12+9pcs leaf spring
Brake(**Service brake**).....Air brake,drum brake
Brake(**Parking brake**).....All-cut off brake

Wheels & Tires

Wheel Type.....stud piloted 10 hole steel disc
Number of Tires.....6+1 (spare tire)
Tire Type/Size.....**8.25R20**
Front: 1860mm
Rear: 1670mm

General Performance Parameters

Max Driving Speed.....95km/h
Ave Fuel Consumption.....≤199g/kW.h
Max Gradeability.....≈30°
Cargo Box Til Angle.....%
Loading Capacity.....10,000kg

Cabin (2080 single and half row)

All-steel frame with 4-point support fully floating suspension and shock absorbers,Adjustable steering wheel, Heating and ventilating system, Exterior sun visor, Adjustable roof flap and Air horn
WITH A/C

Chassis & Dimensions

Overall Dimension.....**7300x2400x3000mm**
(Length x Width x Height)
Wheelbase.....3800mm
Vehicle Overhang.....**Front:** 1160
Rear: 2035
Front/Approach Angle.....18%
Rear/Departure Angle.....20%

Oil Tanker Specifications

Volume.....**6m³**
Tanker body thickness.....4mm
Tanker head thickness.....5mm
Compartment.....2m³ gasoline+4m³ diesel
Others.....Q235 material,explosion-proof cover, pump,bottom valve,refueling gun and hose

Electrical System

Batteries / Voltage.....135ah
2 Quantity
Alternator Voltage.....24V
Operating voltage.....24V

Fuel Tank

Capacity.....150L
Shape / Structure.....Rectangular / Aluminum

PHOTO FOR REFERENCE ONLY



INCLUDED

Fuel Dispenser

